



POLYFRANG®

.223/5.56mm FRANGIBLE AMMUNITION



45 grain Frangible 5.56mm projectile is lead free and environmentally friendly

Velocity comparable to standard .223/5.56mm



PolyFrang .223/5.56mm Frangible Ammunition is for use in training, defense and duty applications. The lead free projectiles are made with Metal Impregnated Polymer (MIP) technology designed to disintegrate upon impact, virtually eliminating ricochets and splashback. PolyFrang maintains lethality while significantly reducing after target collateral damage and over-penetration.

FEATURES AND BENEFITS:

- Lead free projectile is environmentally friendly, reducing cleanup costs
- Reduced ricochet and splashback, allowing for closer engagement within inches of targets
- Reduced damage to steel targets and reduced over-penetration, decreasing range maintenance costs
- Reduced barrel wear and no barrel fouling, reducing armory costs
- Accuracy comparable to standard ammunition out to 100 yards, expanding effective range
- No modifications to duty weapons, saving time and expense

FRANGIBILITY:

- AR500 steel plate – projectiles disintegrate on impact at any angle
- Ballistic gelatin – projectile disintegration begins at ½” and complete at 12”
- No jacket or plating – no shrapnel created
- Rapid energy transfer – extreme lethality into soft targets

For more information or to view our **POLYFRANG®** video visit PolyFrang.com or contact us at sales@PolyFrang.com

BALLISTICS:

- **Bullet Weight:** 45 grains (similar to 62 grain form factor)
- **Velocity:** comparable to standard .223/5.56mm ammunition
- **Lower Chamber Pressure:** reduces weapon platform wear
- **Twist Rate:** Optimized for 1:7 (ideal for military and law enforcement)
- **Functionality:** Cycles in fully-automatic rifles with barrels as short as 10.5" and with suppressors



POLYFRANG®